


<b>Modello / Model</b>  	<b>UM180/3C/TPD</b>
<b>Tipo</b> <i>Type</i>	Digitale / Digital
<b>Dimensioni ingombro</b> <i>Overall dimensions</i>	1800x680x590
<b>Temperatura</b> <i>Temperature</i>	-2°C/+8°C
<b>Vano tecnico</b> <i>Technical compartment</i>	DX
<b>Cassetto 2/3 – gn/1 – H310MM</b> <i>Drawer 2/3 – gn1/1 – h310mm</i>	N° 3
<b>Alimentazione</b> <i>Supply</i>	Elettrica/lectric
<b>Costruzione</b> <i>Building</i>	Acc inox AISI 304 Sc. Brite
<b>Potenza assorbita kW</b> <i>Absorbed power kW</i>	0,282
<b>Voltaggio</b> <i>Voltage</i>	230V/50Hz (60Hz on request)
<b>Resa frigorifera W</b> <i>Yeld Cooling W</i>	565
<b>Gas refrigerante</b> <i>Yeld Cooling W</i>	R404a
<b>Kit ruote girevoli</b> <i>kit whwwls</i>	Optional RG100/4
<b>Volume</b> <i>Yeld Cooling W</i>	1,1
<b>Peso lordo</b> <i>Gross weight</i>	140